

PASSEXAM 問題集

更に上のクオリティ 更に上のサービス



1年で無料進級することに提供する
<http://www.passexam.jp>

Exam : **400-101**

Title : CCIE Routing and Switching
Written Exam

Version : Demo

1. Your NetFlow collector is not working due to a large amount of traffic entering your network which is destined to a single IP address.

Which NetFlow feature allows you to collect the top source hosts for this traffic on the local router?

- A. A NetFlow can export flows only to an external flow collector
- B. show ip cache flow
- C. ip accounting
- D. ip flow-top-talkers

Answer: D

2. When you implement PfR, which IP SLA probe is used to determine the MOS?

- A. jitter
- B. latency
- C. packet loss
- D. throughput

Answer: A

3. Which statement about Type-4 LSA in OSPFv2 is true?

- A. It is present only in the backbone area.
- B. It is generated by each ABR and forwarded in non-stub areas.
- C. It is forwarded in NSSA areas.
- D. It is generated by the ASBR and forwarded throughout the whole OSPF domain.

Answer: B

4. Which three technologies can be used to implement redundancy for IPv6? (Choose three)

- A. IPv6 NA
- B. NHRP
- C. HSRP
- D. DVMRP
- E. GLBP
- F. IPv6 RA

Answer: CEF

5. On a network using DiffServ, which option refers to the actions that applied to a packet as it moves through the network?

- A. DSCP
- B. PHB
- C. Codepoint
- D. IP-precedence

Answer: A