

PASSEXAM 問題集

更に上のクオリティ 更に上のサービス



1年で無料進級することに提供する
<http://www.passexam.jp>

Exam : 642-737

**Title : Implementing Advanced
Cisco Unified Wireless**

Version : DEMO

1.Which two considerations must a network engineer have when planning for voice over wireless roaming? (Choose two.)

- A. Roaming with only 802.1x authentication requires full reauthentication.
- B. Full reauthentication introduces gaps in a voice conversation.
- C. Roaming occurs when e phone has seen at least four APs.
- D. Roaming occurs when the phone has reached -80 dBs or below.

Answer: A,B

2.Which three of the items listed are required configuration parameters for the WLC to enable NAC out-of-band single sign-on when implementing NAC appliances? (Choose three.)

- A. EAP authentication
- B. web authentication
- C. SNMP
- D. RADIUS accounting
- E. WLAN > SNMP NAC enabled
- F. WLAN > RADIUS NAC enabled

Answer: C,D,E

3.An engineer is responding to a man-in-the-middle attack and needs to enable security features to prevent such attacks in the future. What security feature would prevent a manin-the-middle attack?

- A. Management Frame Protection
- B. ACL
- C. Enable client and infrastructure MFP
- D. AAA Override

Answer: C

4.Refer to the exhibit.

The screenshot shows the 'WLANs > Edit' configuration page for a Cisco Wireless LAN Controller (WLC) version 7.0. The 'Security' tab is selected. The 'Client Exclusion' checkbox is checked and set to 'Enabled' with a 'Timeout Value (secs)' of 0. Other settings include 'Allow AAA Override' (unchecked), 'Coverage Hole Detection' (checked), 'Enable Session Timeout' (checked, 1800 secs), 'Aironet IE' (checked), 'Diagnostic Channel' (unchecked), 'IPv6 Enable' (unchecked), 'Override Interface ACL' (None), 'P2P Blocking Action' (Disabled), 'H-REAP Local Switching' (unchecked), 'Learn Client IP Address' (checked), 'DHCP Server' (unchecked), 'DHCP Addr. Assignment' (unchecked), 'Management Frame Protection (MFP)' (Infrastructure MFP Protection checked, MFP Client Protection Optional), 'DTIM Period' (802.11a/n: 1, 802.11b/g/n: 1), and 'NAC State' (unchecked).

What is the effect of setting Client Exclusion to Enabled and set to a Timeout Value of 0 seconds in a Cisco WLC v7.0?

- A. Excluded clients must be manually removed from the excluded list.
- B. Client exclusion will not occur.
- C. Client exclusion timeout will be determined by the IDS module.
- D. Clients will only be disconnected and not excluded.

Answer: A

5.What NAC appliance component is configured to create user roles, meet remediation requirements, and handle checking for device compliance?

- A. NGS
- B. NAA
- C. NAS
- D. NAM

Answer: D