

Exam : CCA AppDS Traffic Management

Title : Deploy and Manage Citrix
ADC 14.x with Traffic
Management

Version : DEMO

1.Which feature can a Citrix Administrator use to create a consistent set of front-end SSL parameters across multiple SSL vServers?

- A. SSL profile
- B. SSL multiplexing
- C. SSL bridge
- D. SSL policy
- E. SSL policy

Answer: A

Explanation:

<https://docs.citrix.com/en-us/citrix-adc/current-release/ssl/ssl-profiles.html>

2.In an SSL offload deployment, which policy will allow a Citrix Administrator to modify all URLs in the response body from "http://" to "https://"?

- A. > add rewrite action Act1 replace_all "HTTP.RES.BODY(200000)" "\"http://\"" -pattern "https://" > add rewrite policy Pol1 trueAct1 NOREWRITE
- B. > add rewrite action Act1 replace_all "HTTP.RES.BODY(200000)" "\"http:\"\" -pattern \"https://\" > add rewrite policy Pol1 trueAct1 NOREWRITE
- C. > add rewrite action Act1 replace_all "HTTP.RES.BODY(200000)" "\"https //\"" -pattern "http://" > add rewrite policy Pol1 trueAct1 NOREWRITE
- D. > add rewrite action Act1 replace_all "HTTP.RES.BODY(200000)" "\"https:\"\" -pattern "http://" > add rewrite policy Pol1 trueAct1 NOREWRITE

Answer: D

3.Scenario: To receive data alerts for failures, a Citrix Administrator is configuring SNMP on the Citrix ADC. The administrator is confident that the manager, alarms and SNMP traps are configured correctly. The following week, there is a Citrix ADC-related outage and the administrator does NOT receive any alerts.

What could be the reason for this alert failure?

- A. The Citrix Web App Firewall is blocking the alerts from going out.
- B. The community name was NOT configured in the Citrix ADC SNMP trap destination settings.
- C. The Citrix ADC only has standard licensing.
- D. The Citrix ADC is configured for SNMP version 1.

Answer: B

4.A Citrix Administrator needs to use a client's IP address as the source IP address for Citrix ADC-to-server connections.

Which Citrix ADC mode can the administrator use to meet this requirement?

- A. USNIP
- B. Layer 2
- C. Layer 3
- D. USIP

Answer: D

Explanation:

When you enable the USIP address mode of a NetScaler appliance, the appliance forwards each packet

to the appropriate back end server with the client IP address.

<https://support.citrix.com/article/CTX121974>

5.Scenario: A Citrix Administrator currently manages a Citrix ADC environment for a growing retail company that may soon double its business volume. A Citrix ADC MPX 5901 is currently handling web and SSL transactions, but is close to full capacity. Due to the forecasted growth, the administrator needs to find a cost-effective solution.

What cost-effective recommendation can the administrator provide to management to handle the growth?

- A. The addition of another MPX 5901 appliance
- B. A hardware upgrade to a Citrix ADC MPX 8905
- C. A license upgrade to a Citrix ADC MPX 5905
- D. A hardware upgrade to a Citrix ADC SDX 15020

Answer: B