

---

**Exam : OSP-002**

**Title : BICSI Outside Plant  
Designer (OSP)**

**Version : DEMO**

---

1.You can keep track of how much cable is left in a box if you \_\_\_\_\_.

- A. Record on the cable box the beginning distance marked on the cable
- B. Read the distance off the cable
- C. Weigh the box
- D. You can't

**Answer: A**

2.What is a passive optical network (PON)?

- A. A point-to-multipoint network architecture in which unpowered optical splitters are used to enable a single optical fiber strand to serve multiple end-points.
- B. A point-to-point network architecture in which powered optical splitters are used to enable a single optical fiber strand to serve multiple end-points.
- C. A point-to-point network architecture in which unpowered optical splitters are used to enable a single optical fiber strand to serve multiple end-points.
- D. A point-to-multipoint network architecture in which powered optical splitters are used to enable a single optical fiber strand to serve multiple end-points.

**Answer: A**

3.A fiber stripper removes the \_\_\_\_\_ of the fiber.

- A. Core
- B. Cladding
- C. Buffer coating

**Answer: C**

4.You can keep track of how much cable is left in a box if you \_\_\_\_\_.

- A. Record on the cable box the beginning distance marked on the cable
- B. Read the distance off the cable
- C. Weigh the box
- D. You can't

**Answer: A**

5.From a reliability standpoint, \_\_\_\_\_ is the best method to join two fibers.

- A. Mechanical splicing
- B. Fusion splicing
- C. Adhesive/polish connectors
- D. Factory terminations

**Answer: B**